

RECEIVED  
CENTRAL FAX CENTER  
AUG 30 2006

015/062

Docket No. F-7882

Ser. No. 10/614,640

### REMARKS

Claims 1-19 remain pending in this application. Claims 1-4, 7 and 20 are rejected. Claims 5, 6 and 8-19 are withdrawn from consideration. Claim 20 is cancelled.

Applicant herein traverses and respectfully requests reconsideration of the rejection of the claims and objections cited in the above-referenced Office Action.

The Examiner objects to the drawings under 37 CFR 1.84(p)(4) for allegedly having different elements identified by common reference designators. It is stated that reference designators 2, 3, 4 and 5 are applied to both dots and sheets. Applicant respectfully traverses this objection.

It is applicant's position that reference characters 2, 3, 4 and 5 are clearly intended to be indicative of the specific colors of cyan, black, magenta and yellow, respectively, to distinguish one from the other, and independent from the specific form in which they happen to be represented. Thus, this meaning is understood be distinguishing of these colors, irrespective of whether reference is made to these colors' appearance as dots, as in Fig. 2, or as part of individual sheets in Figs. 11, 12 and 13. In the specification, the definition of these reference designator numerals consistently, and quite properly, refer to the terms cyan, black, magenta

Docket No. F-7882

Ser. No. 10/614,640

and yellow, and not, as the Examiner avers, dots and sheets. Therefore, based upon the foregoing, reconsideration of the objection to the drawings and withdrawal thereof are earnestly solicited.

The Office Action indicates that a substitute specification in proper idiomatic English and in compliance with 37 CFR 1.52(a) and (b) is required. Applicant submits herewith a substitute specification wherein amendments are effected to place the text thereof into proper English in accordance with 37 CFR 1.125(c). The amendments effected in the specification address each and every alleged problem noted by the Examiner. Also accompanying this amendment is a reproduction of the original specification with markings indicating the amendments effected in the substitute specification relative to the originally filed specification in accordance with MPEP §608.01(q) and 37 CFR 1.125(b). No new matter is added. Entry of the substitute specification is respectfully requested.

Claims 1-4, 7 and 20 are rejected under 35 U.S.C. § 112, first paragraph, as not being enabled by the specification. Claim 20 is cancelled, rendering its rejection moot. Applicant herein respectfully traverses this rejection as pertaining to the remaining claims.

The above cited Office Action states that it is not clear how a dot angle relates to a screen angle. Applicant submits that while the dot angle and the screen angle are ultimately aligned, and therefore the same, determination of the dot angle

Docket No. F-7882

Scr. No. 10/614,640

depends upon a prior empirical, or otherwise, determination of a dot angle that does not produce moire, and then subsequently orienting the screen at a respective angle, i.e. a screen angle, that matches the empirically, or otherwise- determined moire-free dot angle, to thereby produce corresponding dot angles for each of the colors, which, when printed thereby, together do not create moire. Such understanding is clear to one skilled in the art, and therefore provides adequate support for the invention as now claimed.

Claim 20 is rejected under 35 U.S.C. 112, second paragraph, as being indefinite. Claim 20 is cancelled, rendering the rejection moot.

Applicant respectfully requests a one (1) month extension of time for submitting this response. A notice of appeal was received by the U.S. Patent and Trademark Office on May 30, 2006. The fee of \$60 for the extension is provided for in the charge authorization presented in the PTO Form 2038, Credit Card Payment form, provided herewith.

If there is any discrepancy between the fee(s) due and the fee payment authorized in the Credit Card Payment Form PTO-2038 or the Form PTO-2038 is missing or fee payment via the Form PTO-2038 cannot be processed, the USPTO is hereby authorized to charge any fee(s) or fee(s) deficiency or credit any excess payment to Deposit Account No. 10-1250.

Docket No. F-7882


Ser. No. 10/614,640

In light of the foregoing, the application is now believed to be in proper form for allowance of all claims and notice to that effect is earnestly solicited.

It is noted that a Request for Continued Prosecution (RCE) is being filed concurrently herewith.

Respectfully submitted,

JORDAN AND HAMBURG LLP

By   
C. Bruce Hamburg  
Reg. No. 22,389  
Attorney for Applicant

Jordan and Hamburg LLP  
122 East 42nd Street  
New York, New York 10168  
(212) 986-2340

enc: Form PTO-2038; Substitute Specification; and Marked reproduction of original specification.

F-7882

## MARKED SPECIFICATION

Ser. No. 10/614,640

~~Method for manufacturing screen plate and screen plate~~METHOD FOR MANUFACTURING A SCREEN PLATE FOR PRINTING AMOIRE-FREE IMAGE

## BACKGROUND OF THE INVENTION

5

This invention relates to the method for manufacturing of a screen plate and the screen plate that prevent generating of moire such as moire fringes, spot and so on in a screen printing.

10

Conventionally, the number of lines of a screen are 300 lines/inch in the case of the printed matter of a screen-printing, and the screen angle between each color plate is set into 30 degree's difference. The color of yellow is set at 15 degree's difference, for example, 0 degree, 60 degree and so on.

In the conventional manufacture method of the screen plate, the moire such as moire fringes and a spot is generated in the relation with the number of

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

screen lines and a screen angle.

## SUMMARY OF THE INVENTION

In light of the forgoing, it is an object of the invention to provide a the  
method for manufacturing of a screen plate and the screen plate which can  
5 prevent certainly the generating of moire and print a picture with a lively  
motion and with high resolution. It is another object of the invention to provide  
a method for manufacturing of a screen plate and the screen plate that can be  
manufactured the high utility value of a screen plate in the optimal state.

Novel features which are believed to be characteristic of the invention,  
10 both as to its organization and method of operation, together with further  
objects and advantages thereof, are described below with reference to the  
accompanying drawings in which preferred embodiments of the invention are  
illustrated as an example.

It is to be expressly understood, however, that the drawings are for the  
15 purpose of illustration and description only, and are not intended as a definition

MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

of the limits of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a flow chart showing a first embodiment of the present invention;

5           FIG. 2 is a chart showing screen angle of a degree of  
a screen;

FIG. 3 is another chart of another degree of a screen;

10           FIG. 4 is a diagram of a step for forming a screen  
plate;

FIG. 5 is a diagram showing the way in which a T-shirt is printed;

MARKED SPECIFICATION

F-7882

Scr. No. 10/614,640

FIG. 6 is a diagram showing the way in which a can  
is printed;

FIG. 7 is a flow chart showing a second embodiment of the present  
invention;

5 FIG. 8 is a diagram of a process for forming a screen  
plate;

FIG. 9 is a flow chart showing a third embodiment of the present  
invention;

10 FIG. 10 is a diagram when the pattern as a manuscript  
is read with a scanner;

FIG. 11 is a view about a moire prevention process;

FIG. 12 is a diagram for performing from a digital decomposition to a



MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

monochrome-two gray scale;

FIG. 13 is a diagram for performing from gray scale  
conversion to a finishing;

FIG. 14 is a reference view for receiving the data of picture;

5 FIG. 15 is a flow chart showing a fourth embodiment of the present  
invention;

FIG. 16 is a diagram of a step for selecting;

FIG. 17 is a diagram of a step for selecting a color;

FIG. 18 is a diagram of a step for performing the spot  
10 color;

FIG. 19 is a diagram of a step for converting;

MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

FIG. 20 is a diagram of a step for processing a frame;

FIG. 21 is a flow chart showing a fifth embodiment of the present invention;

FIG. 22 is a diagram of a step for processing an  
5 operation;

FIG. 23 is a diagram of a step for saving;

FIG. 24 is a diagram of a step for amending;

FIG. 25 is a flow chart showing a sixth embodiment of the present invention;

10 FIG. 26 is a diagram of a step for forming an under base white;

FIG. 27 is a diagram of a step for forming a top

MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

white;

FIG. 28 is a diagram of a step for forming an under  
base white;

FIG. 29 is a diagram of a step for forming an under  
5 base white;

FIG. 30 is a diagram of a step for forming a top  
white;

FIG. 31 is a diagram of a step for converting an index  
color;

10 FIG. 32 is a diagram of a step for determining the  
number of colors;

FIG. 33 is a diagram of a step for adding the colors;

F-7882

## MARKED SPECIFICATION

Ser. No. 10/614,640

FIG. 34 is a diagram of a step for processing the index color;

FIG. 35 is a diagram of a step for reversing; and

FIG. 36 is a diagram of a step for converting.

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention are described in more detail below with reference to the accompanying drawings.

An understanding of the present invention may be best gained by reference to FIGS. 1-6

10 Referring to Figs. 1 - 6 and 10, according to a first embodiment of a method for manufacturing a screen plate according to the present invention, the method for manufacturing the screen plate ~~printed as~~ which is used to print a net

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

positive by a conventional method after an image to be printed is suitably processed by using a scanner X (See Fig. 10) and changed to the digital image data which can be processed for plate-making, by a computer or the like is produced as a separation net negative (net negative) which is reversed to a net positive image when adhesively applied to the object being printed[[, the]].

Reference numeral 1 shows a step for preventing [[a]] moire. In a first ~~phenomenon~~ aspect of the invention set of screen orientation angles, as shown in a graph having, for example, [[a]] X and Y axes ~~for example~~, as shown in Fig. 2, a dot angle for cyan 2 is set at 79 to 81 degrees, preferably 80degrees; the dot angle for black 3 is set at 51 to 53 degrees, preferably 52 degrees; a dot angle for magenta 4 is set at 21 to 23 degrees, preferably 22 degrees; and a dot angle for yellow is set at 6 to 8 degrees, preferably 7 degrees. Then, spots [[6]] of each color printed at the specified dot angles [[that]] are advantageously formed in the shape of an ellipse ~~are used~~.

In addition, each dot angle in the first ~~phenomenon~~ aspect of the invention set of screen orientation angles which is set up in the first embodiment is also ~~positioned~~ positionable at [[a]] second, third and fourth ~~phenomenon~~ parts set of screen orientation angles, for example, as an opposite angle or a

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

symmetrical angle. For example, as shown in FIG. 3, in the second  
~~phenomenon-part~~ set of screen orientation angles, cyan 2 is set up at 170  
 degrees; black 3 is set up at 142 degrees; magenta 4 is set up at 112 degrees;  
 and yellow 5 is set up at 97 degrees.

5           Moreover, the ~~[[dot]]~~ screen angle that prevents moire generation of  
 spots, etc., printed thereby may be, for example, set up at approximately 6 to 8  
 degrees for cyan 2; approximately 66 to 68 degrees for black 3; approximately  
 126 to 128 degrees for magenta 4; and approximately 170 to 173 degrees for  
 yellow 5. Also each color's ~~[[dot]]~~ screen angle ~~that prevents to generate the~~  
 10 which is determined to prevent generation of moire, when printed, can be set up  
~~freely or alternatively by other angular orientations not limited to the above~~  
angular orientations.

The numeral 7 shows a step for forming a screen plate 11. As shown in  
 FIG. 4, the screen plate 11 includes a screen 9 having a positive film 8 having  
 15 an arbitrary numbers of screen lines, 240 lines in this embodiment and a frame  
 10 made from aluminum. Screen plate 11 is produced by stretching the  
 screen 9 in the level and the perpendicular state by ~~the same method as usual~~ the

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

conventionally practiced method. In this embodiment, the screen 9 is made from DACRON®. DACRON® is a registered trademark of E.I. Du Pont de Nemours and Company, Wilmington, Delaware, for its brand of condensation polymer polyester fiber made from ethylene glycol and terephthalic acid. Also  
5 the frame 10 may be ~~formed in~~ a wooden frame, and the screen 9 may be ~~used~~  
alternatively comprised of silk, as the same as usual, nylon, polyester, ~~[[and]]~~  
or stainless steel and the like.

In addition, the screen 9 is determined in consideration of a printing machine, ink, etc., although the screen about four times as the number of lines  
10 is used basically. For example, the number of the screen lines per inch of the dot screen is approximately 120 mesh (lines) in the case of 30 lines;  
approximately 200 meshes in the case of 50 lines; and approximately 240 meshes in the case of 60 lines.

In this embodiment, ~~[[the]]~~ a dot ~~[[is]]~~ formed in the shape of an ellipse  
15 and is used. Moreover the dot may be formed in the shape of a circle, lozenge, square, line, cross and the like. Furthermore, according to the type of printed matter, a shape suited to the particular application can alternatively be used the

F-7882

## MARKED SPECIFICATION

Ser. No. 10/614,640

~~good shape and favorite shape may be used alternatively.~~

5 The screen plate 11 produced by the above manufacture method of the screen plates is used in order to print to the cloth such as a towel and clothes such as a T-shirt, a trainer, etc., ~~a~~ A T-shirt in this embodiment as shown in FIG. 5, by a roller printing and the like.

With the adjusted screen angle, the generating of moire is prevented efficiently without ~~interfering the dot and mismatching the screen angle in dot decomposition and interference,~~ and the such that a high quality product can be obtained.

10 In addition, although a T-shirt as the printed object is explained in this embodiment, the printed objects including sheet material and processed goods which are processed with papers, fiber, resin material, metal material, ceramics, glass, etc. may be used. For example, it may be printed on the surface of the can, as shown in FIG. 6.



## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

Moreover, the Tombo ( which means "Dragonfly" in Japanese), and which is a mark (eg., crop/registration mark) for arranging direction of a pattern with the film 8 is, as usual, ~~is given to~~ oriented in arbitrary positions.

Other embodiments of the present invention will now be described with  
 5 reference to FIGS. 7-36. In FIGS. 7-36, the same components as in the first embodiment described above with reference to FIGS. 7-36 are designated by the same reference numerals and therefore will not be further explained in great detail.

A second embodiment of the present invention is shown in FIGS. 7 and  
 10 8. It is distinguished from the first embodiment in that the formation process 7 is replaced from another process 7A. In the step 7A, when ~~the delicate gap arises at~~ minor deviation between dots is present at the screen angle set up at the moire prevention step 1, both the screen 9 and the positive film 8 or either one is horizontally rotated to the angle at which there is the no moire condition.  
 15 Then, the screen 9 is fixed to the frame 10 in the position (angle) ~~[[that]]~~ in which there is no moire ~~screen 9 is fixed to the frame 10 in the position (angle)~~ that there is no the moire condition, and a screen plate 11A is thus formed. A

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

screen plate 11A according to the second embodiment has similar advantages to that according to the first embodiment.

In addition, when the screen angle is not set up, the screen 9 may be horizontally rotated to the angle which the moire is lost, the screen 9 may be  
5 fixed to the frame 10 in the position (angle) which the moire is lost, and the screen plate 11A may be created.

A third embodiment of the present invention is shown in FIGS. 9 to 14. It is distinguished from the first embodiment in that the moire prevention process 1 is replaced from another step 1A. In the moire prevention step 1A,  
10 the electronic correction processing is performed for the picture manuscript using the scanners X for making the plate and the like, and electronic data is processed suitably by the FM screen method which expresses a shade by the density without regularity of the dots infinitely formed. In the moire prevention step 1A, as shown in FIG. 10, In this moire prevention step 1A, the pattern as a  
15 manuscript is read with a scanner X as usual or the processed image data is used, and the data is divided by four colors as the printing colors by digital decomposition, that is, cyan 2, magenta 4, yellow 5 and black 3 (S1). Then

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

each divided color is converted by a monochrome-two gray scale, and the input and output resolutions are set the same value, and a conversion system is set as the error conversion spreading method (dither) (S2). After each color is changed into gray scale, and the size ratio is set as "1" (S3), each color changed into the gray scale is specified, and it piles up as one frame (S4) and is printed by the screen 9 by controlling of the terminal.

Thus, since a screen plate 11B according to the second embodiment has similar advantages to that according to the first embodiment and can reduce the size of dot, it can prevent degradation of the quality-of-image by the moire efficiently and can print high resolution over the whole grayscale from a highlight to a shadow.

In addition, as shown in FIG. 14, when the server Y having an input-and output means, a control means to perform a system based on a main program, various databases (DB) which memorize image data information, customer information, etc. and memory means (memory part), etc is set suitably, and it is connected to the communications network Z through radio or the telephone line, so that it can received the image data at any time from consumer terminals

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

including a plurality of the personal computers, a notebook typed PC, PDA, L-mode correspondence telephone, a portable telephone, and Internet-compatible household electric appliances which are connected through the communications network Z and the digital processing can be performed by the method of this  
5 embodiment. Therefore, it can be performed efficiently in a short time from data receipt to completion.

Furthermore, when the data obtained using electronic data processing is used as surface treatment information on the printed object, it combines with the conventional processing methods including the etching processing and sandblast  
10 processing so that the high resolution and high quality picture are reproducible to the printed object.

A fourth embodiment of the present invention is shown in FIGS. 15 to 20. It is distinguished from the third embodiment in that the moire prevention step 1 is replaced from another step 1B. In this moire prevention step 1B, the  
15 electronic data processing is performed by the special-color decomposition by the simulation. The moire prevention step 1B includes a step 13 for selecting, a

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

step 14 for selecting colors, a step 15 for performing the spot colors, a step 16 for converting and a step 17 performing a frame.

5 In the selection step 13, each color is chosen via the simulation by a syringe tool in means for specifying the color range after a based picture (RGB) 12 as the original edition is reproduced by data-processing terminal.

In the color selection step 14, each color chosen at the selection step 13 is saved as a selection range, and the resemble color to the picture 12 is selected.

10 In the spot-color performing step 15, the color chosen and determined at the color selection step 14 transposes to a spot color.

In the conversion step 16, the state that is determined at the spot color-performing step 15 is saved according to each color, and it is converted to the monochrome-two gray scale after it is converted to the gray scale.

15 In the frame processing step 17, each color is selected and piled up as one frame after the color selection process 14, the spot color processing step 15,

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

and the conversion step 16 are processed successively.

In the selection step 13, when each color is chosen, the maximum permissible quantity may be set up moderately, and automatic color range specification including red color, yellow color, green color, cyan color, blue  
5 color, magenta color, highlight, neutral colors, shadow, etc. may be used.

In the conversion step 16, the error conversion spreading method (dither) is used preferably, the setting value of the input resolution and output resolution is set up similarly, and it is performed.

A fifth embodiment of the present invention is shown in FIGS. 21 to 24.  
10 It is distinguished from the fourth embodiment in that the selection process 13 is replaced from another selection process 13A that comprises of an operation step 18, a saving step 19 and an amendment step 20.

In the operation step 18, the reproduced picture is performed by the operation processing after a based picture (RGB) 12 as the original edition is  
15 reproduced by data-processing terminal.

F-7882

## MARKED SPECIFICATION

Ser. No. 10/614,640

In the saving step 19, each color is chosen, reversed the gradation, and saved at a new channel.

In the amendment step 20, the gradation of the image data saved at the step 19 is amended at level.

5 Thus, a moire prevention step 1C chooses each color and can processes so that the moire prevention process 1C according to the fifth embodiment has similar advantages to that according to the fourth embodiment.

A sixth embodiment of the present invention is shown in FIGS. 25 to 36. It is distinguished from the fourth embodiment in that the moire prevention step  
10 s 1A is replaced from another process 1D. In the moire prevention process 1D, the electronic data processing is performed by the special-color decomposition of full color. The moire prevention step 1D is comprised of a step 24 for forming an under base white, a step 27 for forming an top white, a step 28 for converting to index color, a step 29 for determining the number of colors, a  
15 step 30 for adding the colors, a step 31 for processing the index color, a step 34

F-7882

## MARKED SPECIFICATION

Ser. No. 10/614,640

for forming an under base white and a step 35 for finishing.

The forming step 24 further includes a step 21 for coping and pasting the reproduced picture after the based picture (RGB) 12 as the original edition is reproduced by data-processing terminal, and a new channel is created; a step 22  
5 for reversing and converting the picture pasted at this copy step 21; and a step 23 for converting the picture to the monochrome-two gray scale and gray, and save to another name, for example, under base white.

The forming step 27 further includes a step 25 for selecting the white of a highlight portion, at the same time, the white portion in a picture is specified  
10 after the based picture (RGB) 12 as the original edition is reproduced by data-processing terminal; a step 26 for saving the picture as a new channel created; a step 23A for converting the picture saved in the saving step to the monochrome-two gray scale and gray, and save to another name, for example, top white.

In the index color conversion process 28, the picture (RGB) 12 as the  
15 original edition is changed into an index color by the error conversion spreading method (dither), noise method or the pattern method, dither in this embodiment.



## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

In the number determination process 29, the number of colors is determined of the picture changed in the index color conversion process 28.

5 In the color addition step 30, the picture processed in the number determination process 29 is specified at the color range, and each color is selected. Then each selected color is added to a new channel.

In the index color processing step 31, the top white and under base white saved in the top white forming step 27 and the under base white forming step 24 are added to the index color data after the color addition step 30 for every color is performed.

10 The under base white forming process 34 for utilizing the basic color further includes a step 32 for reversing; and a step 33 for converting. The reversing step 32 is performed to select the basic color (color of the background) from the picture (RGB) 12 and reverse the specified range. In the conversion step 33, the reversed picture is added to the new channel, and it  
15 performs the reversal conversion of gradation and is converted to the monochrome-two gray scale and gray scale.

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

The finish step 35 performs to add the under base white created in the under base white forming step 34 to the index color completed at the index color processing step 31.

5 When the base color is not printed, the moire prevention step 1D according to the sixth embodiment has similar advantages to that according to the fourth embodiment.

Furthermore, although each embodiment differs mainly explained based on the first embodiment, even if one uses the present invention combining the composition used for the form of not only this, but each embodiment, the same action effect is acquired.

10

As set forth above, the advantages of the invention are as follows:

(1) A method for manufacturing of a screen plate including the screen printing plate, screen printing plate using an image, electronic stencil and the like in order to print the image to printed object, includes a step for preventing generating of a moire including moire fringes and a spot produced by piling up the formation which the point and line are distributed regularly and

15

## MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

geometrically, one of setting a dot angle of printing colors needed for printing of the screen plate at a predetermined angle for each color (e.g., cyan (C), magenta (M), yellow (Y), and black (K)) and matching a screen angle, which is the angle to which the screen itself is rotated, with the dot angle, in order to  
5 obtain a no moire condition; and a step for forming the screen plate including a screen and a frame stretching the screen so that it can prevent certainly the generating of moire.

Therefore, it can print a picture with a lively motion and with high resolution.

10 (2) As discussed above, since it can prevent ~~certainly~~ the generating of moire, it can be optimally manufactured, while insuring the high utility value of a screen plate ~~in the optimal state~~.